



Dual Diode Modules

Type	V _{RRM}	I _{FAV}	@ T _C	I _{FRMS}	I _{FSM} 150°C 10ms	V _{T0}	r _T	T _{VJM}	R _{thJC}	R _{thCK}	Fig. No.	Config.
➤ New	V	A	°C	A	A	V	mΩ	°C	per Chip			
MDD600-12N1	1200	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	H
MDD600-14N1	1400	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDD600-16N1	1600	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDD600-18N1	1800	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDD600-20N1	2000	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDD600-22N1	2200	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDA600-12N1	1200	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	F
MDA600-14N1	1400	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDA600-16N1	1600	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDA600-18N1	1800	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDA600-20N1	2000	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDA600-22N1	2200	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDK600-12N1	1200	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	I
MDK600-14N1	1400	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDK600-16N1	1600	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDK600-18N1	1800	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDK600-20N1	2000	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDK600-22N1	2200	600	111	1818	21800	0.75	0.2	150	0.062	0.02	W63	
MDD 710-22N1	2200	708	85	1440	12750	0.80	0.35	150	0.062	0.02	W65	G
MDD 710-26N1	2600	708	85	1440	12750	0.80	0.35	150	0.062	0.02	W65	
MDA 710-22N1	2200	708	85	1440	12750	0.80	0.35	150	0.062	0.02	W65	F
MDA 710-26N1	2600	708	85	1440	12750	0.80	0.35	150	0.062	0.02	W65	
MDK 710-22N1	2200	708	85	1440	12750	0.80	0.35	150	0.062	0.02	W65	I
MDK 710-26N1	2600	708	85	1440	12750	0.80	0.35	150	0.062	0.02	W65	
MDD 810-12N1	1200	807	85	1661	17250	0.78	0.23	150	0.062	0.02	W65	H
MDD 810-16N1	1600	807	85	1661	17250	0.78	0.23	150	0.062	0.02	W65	
MDD 810-18N1	1800	807	85	1661	17250	0.78	0.23	150	0.062	0.02	W65	
MDA 810-12N1	1200	807	85	1661	17250	0.78	0.23	150	0.062	0.02	W65	F
MDA 810-16N1	1600	807	85	1661	17250	0.78	0.23	150	0.062	0.02	W65	
MDA 810-18N1	1800	807	85	1661	17250	0.78	0.23	150	0.062	0.02	W65	
MDK 810-12N1	1200	807	85	1661	17250	0.78	0.23	150	0.062	0.02	W65	I
MDK 810-16N1	1600	807	85	1661	17250	0.78	0.23	150	0.062	0.02	W65	
MDK 810-18N1	1800	807	85	1661	17250	0.78	0.23	150	0.062	0.02	W65	
MDO1200-14N1	1400	1200	111	1818	21800	0.75	0.2	150	0.062	0.02	W66	J
MDO1200-16N1	1600	1200	111	1818	21800	0.75	0.2	150	0.062	0.02	W66	
MDO1200-18N1	1800	1200	111	1818	21800	0.75	0.2	150	0.062	0.02	W66	
MDO1200-20N1	2000	1200	111	1818	21800	0.75	0.2	150	0.062	0.02	W66	
MDO1200-22N1	2200	1200	111	1818	21800	0.75	0.2	150	0.062	0.02	W66	



W63



W65



W66

Outlines on pages O-01...O-24

